

Chargeurs industriels



Tension Nom.	Pb Ouvert (Ah)			Référence Chargeur	Tension Secteur (VAC)	P Maxi (KVA)	Poids (Kg)	Format
	10h	12h	14h					

12 Volts	55	65	80	M S 12 10	1x230V	0,2	13	1M
	85	100	115	M S 12 15	1x230V	0,3	14	1M
	110	130	155	M S 12 20	1x230V	0,4	14	1M
	140	165	200	M S 12 25	1x230V	0,5	15	1M
	160	200	230	M S 12 30	1x230V	0,5	15	1M
	225	270	310	M S 12 40	1x230V	0,7	16	1M
	280	335	390	M S 12 50	1x230V	0,9	19	1M
	335	400	460	M S 12 60	1x230V	1,1	24	1M
	445	530	615	M S 12 80	1x230V	1,4	27	1M
	560	670	770	M S 12 100	1x230V	1,8	33	1M
670	800	920	M S 12 120	1x230V	2,2	43	2M	

24 Volts	55	65	80	M S 24 10	1x230V	0,4	15	1M
	85	100	115	M S 24 15	1x230V	0,5	16	1M
	110	130	155	M S 24 20	1x230V	0,7	17	1M
	160	200	230	M S 24 30	1x230V	1,1	19	1M
	225	270	310	M S 24 40	1x230V	1,4	24	1M
	280	335	390	M S 24 50	1x230V	1,8	27	1M
	335	400	460	M S 24 60	1x230V	2,2	33	1M
	335	400	460	T S 24 60	3x400V	2,2	47	1T
	445	530	615	M S 24 80	1x230V	2,9	35	1M
	445	530	615	T S 24 80	3x400V	2,9	49	1T
	560	670	770	M S 24 100	1x230V	3,6	57	2M
	560	670	770	T S 24 100	3x400V	3,6	52	1T
	670	800	920	M S 24 120	1x230V	4,3	62	2M
	670	800	920	T S 24 120	3x400V	4,3	55	1T
	780	935	1075	M S 24 140	1x230V	5	66	2M
	780	935	1075	T S 24 140	3x400V	5	58	1T
	890	1070	1230	T S 24 160	3x400V	5,8	62	1T
	1000	1200	1390	T S 24 180	3x400V	6,5	73	1T

36 Volts	110	130	155	M S 36 20	1x230V	1,1	18	1M
	140	165	200	M S 36 25	1x230V	1,4	20	1M
	160	200	230	M S 36 30	1x230V	1,6	20	1M
	225	270	310	M S 36 40	1x230V	2,2	25	1M
	280	335	390	M S 36 50	1x230V	2,7	28	1M
	335	400	460	M S 36 60	1x230V	3,2	35	1M
	335	400	460	T S 36 60	3x400V	3,2	52	1M
	445	530	615	M S 36 80	1x230V	4,3	37	1M
	445	530	615	T S 36 80	3x400V	4,3	54	1T
	560	670	770	M S 36 100	1x230V	5,4	69	1M
	560	670	770	T S 36 100	3x400V	5,4	59	1T
	670	800	920	M S 36 120	1x230V	6,5	76	2M
	670	800	920	T S 36 120	3x400V	6,5	67	1T
	780	935	1075	T S 36 140	3x400V	7,6	77	1T
	890	1070	1230	T S 36 160	3x400V	8,6	81	1T
	1000	1200	1390	T S 36 180	3x400V	9,7	84	1T

48 Volts	160	200	230	M S 48 30	1x230V	2,2	31	1M
	225	270	310	M S 48 40	1x230V	2,9	33	1M
	280	335	390	M S 48 50	1x230V	3,6	36	1M
	335	400	460	M S 48 60	1x230V	4,3	38	1M
	335	400	460	T S 48 60	3x400V	4,3	57	1T
	445	530	615	M S 48 80	1x230V	5,8	70	2M
	445	530	615	T S 48 80	3x400V	5,8	61	1T
	560	670	770	M S 48 100	1x230V	7,2	79	2M
	560	670	770	T S 48 100	3x400V	7,2	63	1T
	670	800	920	M S 48 120	1x230V	8,6	93	2M
	670	800	920	T S 48 120	3x400V	8,6	71	1T
	780	935	1075	T S 48 140	3x400V	10,1	81	1T
	890	1070	1230	T S 48 160	3x400V	11,5	87	1T
	1000	1200	1390	T S 48 180	3x400V	13	88	1T

72 Volts	335	400	460	M S 72 60	1x230V	6,5	69	2M
	335	400	460	T S 72 60	3x400V	6,5	71	1T
	445	530	615	M S 72 80	1x230V	8,6	71	2M
	445	530	615	T S 72 80	3x400V	8,6	74	1T
	560	670	770	M S 72 100	1x230V	10,8	97	2M
	560	670	770	T S 72 100	3x400V	10,8	81	1T
	670	800	920	M S 72 120	1x230V	13	103	2M
	670	800	920	T S 72 120	3x400V	13	88	1T
	780	935	1075	T S 72 140	3x400V	15,1	105	1T
	890	1070	1230	T S 72 160	3x400V	17,3	113	1T
1000	1200	1390	T S 72 180	3x400V	19,4	131	2T	

80 Volts	335	400	460	M S 80 60	1x230V	7,2	71	2M
	335	400	460	T S 80 60	3x400V	7,2	73	1T
	445	530	615	M S 80 80	1x230V	9,6	95	2M
	445	530	615	T S 80 80	3x400V	9,6	77	1T
	560	670	770	M S 80 100	1x230V	12	100	2M
	560	670	770	T S 80 100	3x400V	12	83	1T
	670	800	920	M S 80 120	1x230V	14,4	105	2M
	670	800	920	T S 80 120	3x400V	14,4	90	1T
	780	935	1075	T S 80 140	3x400V	16,8	114	2T
	890	1070	1230	T S 80 160	3x400V	19,2	117	2T
	1000	1200	1390	T S 80 180	3x400V	21,6	133	2T

Chargeurs MS-TS

Charge normale
Plomb Ouvert 12h





Chargeurs PX

Programmable toutes batteries
 Plomb Ouvert - GEL - AGM



Tension Batterie	Référence Chargeur	Pb (Ah)			Gel (Ah)		Courant Nominal (A)	Dimensions			Tension Secteur (V)	Courant secteur Maxi	Poids (Kg)
		8h	10h	13h	12h-14h	L		P	H				
12 V	PX1212M	30/80	30/120	30/140	30	120	2.5/12	250	120	65	1x230	1,8	1,3
	PX1225M	100/160	100/240	100/300	100	240	8/25	250	120	65	1x230	3,2	1,3
24 V	PX2412M	30/80	30/120	30/140	30	120	2.5/12	250	120	65	1x230	3	1,3
	PX2420M	80/120	80/200	80/240	80	200	6/20	250	120	65	1x230	4,6	1,5
	PX2430M	120/180	120/300	120/360	120	300	10/30	275	145	80	1x230	7	2,3
	PX2460M	180/360	180/600	180/720	180	600	15/60	345	175	95	1x230	12	3,9
	PX2490PFC	270/540	270/900	270/1080	270	900	22.5/90	460	305	100	1x230	13	7,2
	PX24120T	360/720	360/1200	360/1400	360	1200	30/120	580	335	130	3x400	7,8	10,9
PX24240T	720/1400	720/2400	720/2800	720	2400	60/240	620	435	265	3x400	15,6	21,5	
36 V	PX3620M	80/120	80/200	80/240	80	200	6/20	275	145	80	1x230	6,9	2,3
	PX3640M	160/240	160/400	160/480	160	400	13/40	345	175	95	1x230	12	3,9
	PX3670PFC	180/420	180/700	180/840	180	700	15/70	460	305	100	1x230	16	7,2
	PX3680T	300/480	300/800	300/960	300	800	25/80	580	335	130	3x400	7,8	11,3
	PX36120T	360/720	360/1200	360/1400	360	1200	30/120	580	335	130	3x400	11,5	11,5
	PX36160T	600/960	600/1600	600/1900	600	1600	50/160	620	435	265	3x400	15,6	22,7
PX36240T	720/1400	720/2400	720/2800	720	2400	60/240	620	435	265	3x400	23	23	
48 V	PX4815M	60/80	60/160	60/180	60	160	5/15	275	145	80	1x230	6,8	2,3
	PX4830M	120/180	120/300	120/360	120	300	10/30	345	175	95	1x230	12	3,9
	PX4855PFC	180/330	180/540	180/540	180	540	15/55	460	305	100	1x230	16	7,2
	PX4865PFC	180/420	180/660	180/780	180	660	15/65	460	305	100	1x230	20	7,2
	PX4880T	300/480	300/800	300/960	300	800	20/80	580	335	130	3x400	10,5	11,3
	PX48120T	360/720	360/1200	360/1400	360	1200	30/120	580	335	130	3x400	15,6	11,5
PX48160T	600/960	600/1600	600/1900	600	1600	50/160	620	435	265	3x400	21	22,7	
PX48240T	720/1400	720/2400	720/2800	720	2400	60/240	620	435	265	3x400	31,2	23	
72 V	PX7220M	80/120	80/200	80/240	80	200	6/20	345	175	95	1x230	12	3,9
	PX7240PFC	160/240	160/400	160/480	160	400	13/40	460	305	100	1x230	20	7,2
	PX7280T	300/480	300/800	300/960	300	800	20/80	580	335	130	3x400	15,6	12,3
	PX72120T	360/720	360/1200	360/1400	360	1200	30/120	620	435	265	3x400	23,4	23,2
PX72160T	600/960	600/1600	600/1900	600	1600	50/160	620	435	265	3x400	31,2	24,7	
80 V	PX8020M	80/120	80/200	80/240	80	200	6/20	345	175	95	1x230	14	3,9
	PX8040PFC	160/240	160/400	160/480	160	400	13/40	460	305	100	1x230	20	7,2
	PX8080T	300/480	300/800	300/960	300	800	20/80	580	335	130	3x400	16	12,3
	PX80120T	360/720	360/1200	360/1400	360	1200	30/120	620	435	265	3x400	24	23,2
	PX80160T	600/960	600/1600	600/1900	600	1600	50/160	620	435	265	3x400	32	24,7

Alimentation Monophasée 230 V ou Triphasée 400 V



Chargeurs MD-TD

Charge rapide

Plomb Ouvert 8h



Tension Nom.	Pb Ouvert (Ah)			Référence Chargeur	Tension Secteur (VAC)	P Maxi (KVA)	Poids (Kg)	Format
	7h	7h30	8h					
24 Volts	230	265	300	M D 24 60	1x230V	2,2	27	1M
	230	265	300	T D 24 60	3x400V	2,2	55	1T
	310	355	400	M D 24 80	1x230V	2,9	30	1M
	310	355	400	T D 24 80	3x400V	2,9	59	1T
	385	443	500	M D 24 100	1x230V	3,6	35	2M
	385	443	500	T D 24 100	3x400V	3,6	68	1T
	460	530	600	M D 24 120	1x230V	4,3	41	2M
	460	530	600	T D 24 120	3x400V	4,3	78	1T
	540	620	700	T D 24 140	3x400V	5	81	1T
	615	708	800	T D 24 160	3x400V	5,8	85	1T
695	798	900	T D 24 180	3x400V	6,5	87	1T	
770	885	1000	T D 24 200	3x400V	7,2	92	1T	
36 Volts	230	265	300	T D 36 60	3x400V	3,2	58	1T
	310	355	400	T D 36 80	3x400V	4,3	61	1T
	385	443	500	T D 36 100	3x400V	5,4	70	1T
	465	533	600	T D 36 120	3x400V	6,5	81	1T
	540	620	700	T D 36 140	3x400V	7,6	83	1T
	615	708	800	T D 36 160	3x400V	8,6	87	1T
695	798	900	T D 36 180	3x400V	9,7	89	1T	
48 Volts	230	265	300	M D 48 60	1x230V	4,3	29	2M
	230	265	300	T D 48 60	3x400V	4,3	59	1T
	310	355	400	M D 48 80	1x230V	5,8	32	2M
	310	355	400	T D 48 80	3x400V	5,8	65	1T
	385	443	500	M D 48 100	1x230V	7,2	37	2M
	385	443	500	T D 48 100	3x400V	7,2	68	1T
	465	533	600	M D 48 120	1x230V	8,6	43	2M
	465	533	600	T D 48 120	3x400V	8,6	75	1T
	540	620	700	T D 48 140	3x400V	10,1	78	1T
	615	708	800	T D 48 160	3x400V	11,5	83	1T
695	798	900	T D 48 180	3x400V	13	87	1T	
770	885	1000	T D 48 200	3x400V	14,4	92	1T	
72 Volts	230	265	300	T D 72 60	3x400V	6,5	71	1T
	310	355	400	T D 72 80	3x400V	8,6	75	1T
	385	443	500	T D 72 100	3x400V	10,8	82	1T
	465	533	600	T D 72 120	3x400V	13	94	1T
	540	620	700	T D 72 140	3x400V	15,1	97	1T
	615	708	800	T D 72 160	3x400V	17,3	101	1T
695	798	900	T D 72 180	3x400V	19,4	105	2T	
80 Volts	230	265	300	T D 80 60	3x400V	7,2	76	1T
	310	355	400	T D 80 80	3x400V	9,6	81	1T
	385	443	500	T D 80 100	3x400V	12	87	1T
	465	533	600	T D 80 120	3x400V	14,4	94	1T
	540	620	700	T D 80 140	3x400V	16,8	119	2T
	615	708	800	T D 80 160	3x400V	19,2	124	2T
695	798	900	T D 80 180	3x400V	21,6	125	2T	